MV-CT*M/CU0200/R

20 MP USB 3.0 Area Scan Camera





GENICAM

USB3 VISION

Introduction

Designed for industrial applications, MV-CT*M/CU0200/R camera offers industry-leading performance and reliability, with various versions to meet diverse application needs. It supports IP67 protection, expanded interfaces, and integration of liquid/electric lenses, light sources, and lens cap, creating a more flexible and efficient system.

Key Features

- The devices with PRO version and MAX version support waterproof connector.
- The devices with PRO version and MAX version adopt precision temperature control design for fast heat balance.
- The color devices with PRO version and MAX version support auto color correction based on multi-spectral fusion technology.
- The device with MAX version integrates lens and light source, enabling lens focusing and light source control.
- Adopts Type-C interface and supports higher transmission bandwidth.
- Compatible with USB3 Vision Protocol, GenICam Standard, and the third-party software based on the protocol and standard.


Applicable Industry

Electronic semiconductor, factory automation, food and beverage, medicine packaging, etc.


Available Models

- Mono camera (BASE): MV-CT0MU0200/R/NN/NN
- Color camera (BASE): MV-CT0CU0200/R/NN/NN

Sensor Quantum Efficiency



MV-CT*MU0200/R




MV-CT*CU0200/R

Specification

Model	MV-CT*MU0200/R	MV-CT*CU0200/R
Performance		
Sensor type	CMOS, rolling shutter	
Sensor model	Sony IMX183	
Pixel size	2.4 μm × 2.4 μm	
Sensor size	1"	
Resolution	5472 × 3648	
Max. frame rate	19.3 fps @ 5472 × 3648 Mono 8	19.3 fps @ 5472 × 3648 Bayer GB 8
Dynamic range	66.1 dB	
SNR	41.3 dB	
Gain	0 dB to 24 dB	
Exposure time	14 μs to 0.86 sec	
Exposure mode	Off/Once/Continuous exposure mode, supports Trigger Width and Trigger Controlled	
Mono/color	Mono	Color
Pixel format	Mono 8/10/10Packed/12/12Packed	Mono 8, Bayer GB 8/10/10Packed/12/12Packed, YUV422Packed, YUV422_YUYV_Packed, RGB 8, BGR 8
Binning	Supports 1 × 1, 2 × 2, 4 × 4	
Decimation	Supports 1 × 1, 2 × 2, 4 × 4	
Reverse image	Supports horizontal and vertical reverse image output	
Electrical features		
Data interface	USB 3.0, compatible with USB 2.0	
Data interface type	Type-C interface	
Control interface	BASE: Not supported	
Digital I/O	8-pin M8 A-Code aviation connector provides power and I/O, including opto-isolated input × 1 (Line 0), opto-isolated output × 1 (Line 1), bi-directional non-isolated I/O × 1 (Line 2).	
Power supply	9 VDC to 24 VDC, supports USB 3.0 power supply	
Power consumption	BASE: Typ. 1.6 W @ 5 VDC (USB 3.0 provides power supply)	BASE: Typ. 1.7 W @ 5 VDC (USB 3.0 provides power supply)
Mechanical		
Lens mount	C-mount	
Dimension	BASE: 29 mm × 29 mm × 30 mm (1.1" × 1.1" × 1.2")	
Weight	BASE: Approx. 72 g (0.2 lb.)	
Ingress protection	BASE: IP40 (under proper lens installation and wiring)	
Temperature	Working temperature: –30 °C to 60 °C (–22 °F to 140 °F) Storage temperature: –30 °C to 80 °C (–22 °F to 176 °F)	
Humidity	20% RH to 95% RH (no condensation)	
General		
Lens mount	MVS or third-party software meeting with USB3 Vision Protocol	
Dimension	32/64-bit Windows 7/10, 64-bit Windows 11, 32/64-bit Linux	
Weight	USB3 Vision, GenICam	
Ingress protection	CE, RoHS, KC	

Dimension

BASE



Unit: mm

MaxxVision®
Sigmaringer Str. 121
70567 Stuttgart
Tel.: 0711 997 996 3
www.maxxvision.com

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.
Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.